






























- **New design**
- **Thermal ticket printer**
(speed 150 mm/s)
- **7-inch Touchscreen for Driver**
- **4.3-inch Touchscreen for User**
- **Validation light feedback with Smart LED RGB**
- **Contactless validation:**
Calypso, DESFire, MIFARE, **EMV Bank cards** and **NFC smartphone**
- **CB2D validation**

Specifications

	Processor	i.MX6 DualLite, dual core Cortex A9 @ 800MHz, 1G DDR3 RAM, 4GB eMMC
	Operating System	LINUX YOCTO
	SD	8GB Industrial quality- Expandable
	Date and Time	RTC
	Driver Display	TFT 7" 1200 cd/m2 Touch Resolution 480x800 px
	User Display	TFT 4,3" 400 cd/m2 Touch Resolution 480x272 px
	Light feedback	RGB
	Printer	Thermal ticket printer speed 150 mm/s resolution 203 dpi (8 dots/mm)
	Audio	Stereo 3W x 2 cone-less
	Interfaces	RS-232 RS-485 2 IN 1 OUT
	Weight	2000g
	Dimensions (mm)	Width 252 x Height 144 x Depth 195
	Temperature (°C)	Min -20° Max +55°
	Contactless reader	PCI PTS POI 6 EMV L1 L2
	Payment Certifications	International schema (i.e. MasterCard, VISA, MC) & Local (Bancomat, CB)
	SAM	4
	Optical reader	YES 1D/2D
	Ethernet	YES
	WIFI	YES
	Bluetooth	YES
	Modem	4G
	USB	YES
	GPS	YES
	Certifications	CE (RED, RoHS, WEEE), ECE R10, ECE R118
	Power supply	24 V cc
	IK Level	08
	IP Index	40